

AT- Advanced Technology

RLFA 2000, Rescue Pumper



According to ÖBFV-RL / Austria



Base specification

- **Chassis:**
 - › Type: MAN TGM 18,290 BB 4x4 Euro 5
 - › Engine output: 213 kW (290 hp) at 2,300 RPM
 - › Transmission: ZF 12 AS 1210 OD MAN Tipmatic
 - › Wheelbase: 3,900 mm
 - › Color coding for handles and controls
 - › LED compartment lighting k
- **Driving compartment:**
 - › Crew: 1 + 8
 - › Rosenbauer crew cab integrated into vehicle body with a total of 3 SCBA COMFORT brackets
 - › Crew cab doors glass/glass
 - › Rotating steps
- **Vehicle body:**
 - › Rosenbauer aluminum body made from self-supporting screwed and bonded aluminum sheets and profile construction with aluminum sandwich sheets and robust plastic covers
- **Equipment compartment:**
 - › Full height lockers and COMFORT rotating compartments for optimal retrieval and secure storage of equipment.
- **Control system:**
 - › Rosenbauer LCS 2.0 (Logic Control System) based on CAN-bus technology for: rotating beacons, horn, front flashlights, scene lighting, remote generator start and monitoring, "engine data," jump-starting, chassis tank indicator, pump, etc.
- **Extinguishing system:**
 - › Type: Normal pressure pump NH35 (FPN 10-3000 and FPH 40-400 according to DIN EN 1028) with LCS 2.0 display control and central water axis
 - › Water tank content: 2,000 l with automatic level regulation
 - › Foam tank 200 l
 - › 3-stage LP FIXMIX
- **Rapid intervention hose reel:**
 - › HP rapid intervention hose reel equipment compartment 5
 - › HP rapid intervention hose reel equipment compartment 7

AT- Advanced Technology

RLFA 2000, Rescue Pumper



- Pressure outlets:
 - › 2 x manual discharge outlets left and right
- Light mast:
 - › Rosenbauer FLEXILIGHT 8 x 35 W LED
- Electrical system:
 - › Martin fire compressor horn with 4 bells
 - › Rosenbauer cab roof extension with integrated LED modules
 - › 2 LED flashing lights in radiator grille
- Additional equipment:
 - › Hygiene board
 - › LED roof lighting
 - › High-end LED crew cab lighting
 - › LED maneuvering lights mounted on mirrors
 - › Reversing and front camera with image representation on the front display
 - › Wing-mounted access plate in area of rear axle
 - › Undervoltage protection
 - › LED traffic control unit
 - › Scene lighting with 6 LED floodlights each along the roof trim on the left and right
 - › Two helmet mounts in the driver's cab, including LED lighting
 - › Power windows
 - › Central locking for driver's cab / crew cab
 - › Rosenbauer RM24M water/foam monitor
 - › EPS-XS (electric power system)
 - › Remote generator start
 - › Roof box with LED lighting
 - › HD hose reels
 - › Damped inlet flap



Dimensions and weight

L x W x H	7,600 x 2,500 x 3,400 mm
Permissible total weight	15,000 kg

Contact

Rosenbauer Österreich GmbH
Paschinger Strasse 90
4060 Leonding, Austria
Tel.: +43 732 6794-0
Fax: +43 732 6794-84

www.rosenbauer.com

 www.facebook.com/rosenbauergroup

Text and images non-binding. The images may depict special editions that are only available at an additional charge.
Subject to change due to technical advances.

Vers. 1.0
BSta, 31.03.2015